

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**



PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant : Anders Bengt Ingemar Hallin et al.
Serial No.: 10/760,564
Filed: January 20, 2004
Title: "HEAT EXCHANGER ARRANGEMENT"
Docket No.: 36381

LETTER


Commissioner of Patents
P.O. Box 1450
Alexandria, VA 22313-1450

Sir/Madam:

Enclosed is a certified copy of Sweden Patent Application No. 0303235-6, filed December 1, 2003; the priority of which has been claimed in the above-identified application.

Respectfully submitted,

PEARNE & GORDON LLP


Jeffrey J. Sopko, Reg. No. 27676

1801 East 9th Street
Suite 1200
Cleveland, Ohio 44114-3108
(216) 579-1700

April 6, 2004

I hereby certify that this correspondence is being deposited with the United States Postal Service as first class mail in an envelope addressed to: Commissioner of Patents, P.O. Box 1450, Alexandria, Va. 22313-1450 on the date indicated below.

Jeffrey J. Sopko

Name of Attorney for Applicant(s)

04/06/2004

Date


Signature of Attorney

PRV

PATENT- OCH REGISTRERINGSVERKET
Patentavdelningen

Intyg Certificate

Härmed intygas att bifogade kopior överensstämmer med de handlingar som ursprungligen ingivits till Patent- och registreringsverket i nedannämnda ansökan.

This is to certify that the annexed is a true copy of the documents as originally filed with the Patent- and Registration Office in connection with the following patent application.

(71) *Sökande Dometic Sweden AB, Solna SE*
Applicant (s)

(21) *Patentansökningsnummer 0303235-6*
Patent application number

(86) *Ingivningsdatum 2003-12-01*
Date of filing

Stockholm, 2004-03-09

För Patent- och registreringsverket
For the Patent- and Registration Office

Hjördis Segerlund
Hjördis Segerlund

Avgift
Fee 170:-

Field of the invention

The present invention relates to a heat exchanger arrangement for a refrigerator cabinet, which evaporator comprises an evaporator tube for conducting a refrigerating medium, a heat exchanger with at least one heat conducting member which is arranged in heat conducting contact with a portion of the evaporator tube and; a heat generating element for defrosting the heat exchanger, which element is arranged in heat conducting contact with the heat conducting member.

- 10 The invention also relates to a refrigerator cabinet comprising such an arrangement. The evaporator according to the invention is particularly useful in connection to absorption refrigerators.

Background of the invention

- 15 Modern refrigerator cabinets may comprise one compartment or several compartments kept at different temperatures. For household applications and also for mobile applications, such as in mobile homes and caravans, the refrigerator may comprise a freezer compartment kept at approx. -18°C and a fridge compartment kept at approx. $+5^{\circ}\text{C}$. The refrigerator comprises a refrigerator apparatus including a condenser and an evaporator. Compressor refrigerators further comprise a compressor, whereas absorption refrigerators instead further comprise a boiler and an absorber. The evaporator comprises an evaporator tube for conducting a cooling medium. The evaporator tube is arranged so that it passes inside the compartment or compartments, which is or are to be cooled by the refrigerator apparatus. For enhancing the heat transfer from the air in the compartments to the cooling medium, a heat exchanger is arranged in heat conducting contact with a portion of the evaporator tube arranged in the respective compartment. The main function of the heat exchanger generally

is to enlarge the surface area of the heat conducting material, which is in contact with the air to be cooled and the cooling medium in the evaporator tube. For this purpose the heat exchanger typically comprises a plurality of fins, which are arranged in heat conducting contact with the evaporator tube.

During normal operation of the refrigerator cabinet, humid air enters into the compartments e.g. when the cabinet doors are opened. As the humidity condenses on the cold surfaces inside the compartments, frost is created on these cold surfaces. Such development of frost is particularly severe on the coldest surfaces, i.e. on the evaporator tube and the heat exchanger in the freezer compartment. The formation of frost on the heat exchanger deteriorates the heat transfer from the air to the cooling medium and thereby lowers the cooling power of the compartment. If the refrigerator apparatus is not dimensioned to compensate for such loss in heat transfer, the temperature in the compartment rises, while jeopardizing the condition of the foodstuff stored in the compartment or the maximum possible storage time. In order to solve this problems, modern refrigerators may comprise means for defrosting the heat exchanger at regular intervals. In such case, the defrosting means is normally applied to the heat exchanger in the freezer, but it may also be applied in the fridge.

US 4,432,211 describes a defrosting apparatus for defrosting the heat exchanger or cooler of a refrigerator. The heat exchanger comprises a plurality of rectangular fins, which are arranged in heat conducting contact with the evaporator tube. The evaporator tube is formed as a coil, comprising two parallel coil portions, each portion comprising a number of straight horizontal tube sections arranged one above the other

and connected one to the other by vertically oriented U-shaped tube bends. The two coil portions are connected to each other by a horizontally oriented U-shaped tube bend. The evaporator coil thus comprises two coil portions, generally extending in
5 respective vertical extension planes arranged next to each other. The rectangular fins extend parallel to each other in respective vertical extension planes, which are perpendicular to the vertical extension planes of the coil portions. The straight tube sections of both coil portions are arranged
10 through openings arranged in a mid portion, between the edges of each fin. The evaporator tube makes contact with the fins at each opening for conducting heat from the fin to the cooling medium inside the tube. This arrangement allows for air to be cooled to pass between the fins and thereby to
15 contact the surfaces of the fins and the evaporator tube sections arranged between the fins, whereby heat may be conducted from the air to the cooling medium.

The US 4,432,211 arrangement further comprises means for defrosting the fins and the evaporator coil. This defrosting
20 means consists of a heater element, which is attached to the vertical edges of the fins, either on one or on both opposite sides of the fins.

WO 03/008880 A1 describes a similar arrangement where the evaporator coil is arranged perpendicular to the fins and
25 through openings arranged in the fins. A heating element in the form of a resistive sheet is arranged in contact with the edges of the fins, at one side of the evaporator coil. For enhancing the heat transfer from the resistive film to the fins, the edge portion of the fins may be L-shaped such that
30 the contact area between the film and the fins is enlarged.

Both the above described arrangements functions in generally the same manner. The heating element is activated at regular intervals. Thereby, heat is generated and conducted from the heating element to the fins and further to the evaporator tube. The so achieved heating of the fins and the evaporator tube melts any frost, which is formed on these members. Control means may be provided for turning off the heating element when all frost has been melted.

Even though the above-described defrosting arrangements may achieve full defrosting of the heat exchanger, they are also impaired with some disadvantages. A major disadvantage concerns the arrangement of the heating element in relation to the fins and the evaporator tube. In both the prior art arrangements, the evaporator tube is arranged through openings arranged in mid portions, between the edges, of the fins. The heating element on the other hand, is arranged in contact with one edge of the fins. This means that there will always be a portion of each fin which is arranged on the opposite side of the evaporator tube as seen from that edge of the fin, which is in contact with the heating element. Expressed differently, a portion of each fin is located at a greater distance from the heating element than the opening surrounding the evaporator tube.

As a consequence, defrosting heat generated by the heating element always has to be transferred past the opening and the evaporator tube in each fin, before it reaches that portion of the fin, which is arranged on the remote side of the opening, for defrosting this remote portion. Therefore a substantial amount of defrosting heat is transferred to and absorbed by the cooling fluid in the evaporator tube, instead of being used for defrosting the remote portion of the fins.

This arrangement is most unfavorable for several reasons.

Firstly, the time needed for defrosting the entire heat exchanger is prolonged, since a substantial part of the generated heat is lost and not used for defrosting. For the same reason the total energy consumption of the heating element is increased. Secondly and even more important, especially at absorption refrigerators, the cooling power of the entire refrigerator cabinet is decreased since the temperature of the cooling medium in the evaporator tube rises when the medium absorbs additional heat from the defrosting heater. Due to the increase in cooling medium temperature, the ability of the evaporator to absorb heat from the air in the refrigerator compartments and thereby to maintain these compartments at the desired temperature is decreased. This is true not only for the compartment in which the defrosting heater works, but also for any compartment cooled by a portion of the entire evaporator tube, which portion is arranged downstream of the evaporator portion in contact with the defrosted heat exchanger. Normally in dual or multi compartment refrigerators, defrosting devices are applied to the heat exchanger serving the freezer compartment. Since the freezer compartment needs the coldest evaporator temperature, this compartment is cooled by the coldest, i.e. most upstream portion of the entire evaporator tube. Hence, the defrosting heat transferred from the defrosting heater to the heat exchanger in the freezer, adversely affects the cooling power of all the compartments in the refrigerator.

Even if the refrigeration apparatus and thereby the circulation of cooling medium in the evaporator tube, is stopped during defrosting, the same problems occurs. In such case, the volume of cooling medium actually present in that portion of the evaporator tube, which is arranged in proximity

to the defrosted heat exchanger, will be heated to a higher temperature. After completion of the defrosting cycle and upon restart of the cooling medium circulation, this volume of cooling medium will have to be even more reduced in
5 temperature by the refrigeration process before it can restart to absorb heat from the compartments.

A further problem associated with the above described prior art defrosting arrangements is that heat is not evenly distributed over the fins. Due to the arrangement of the
10 evaporator tube and the fins, the resistance to heat transfer through the material of the fins will be different at different portions of the fins. This leads to significant disadvantages during defrosting as well as during normal operation of the refrigerator. During normal operation, the
15 uneven heat distribution over the fins will lead to that frost develops more rapidly at some colder portions of the fins than on other portions. Such local development of frost might cause the air passages between the fins to be blocked, whereby defrosting is required more often than what would be needed at
20 an even distributed development of frost.

During defrosting, the uneven distribution of frost over the fins leads to inefficient defrosting. The areas on which less frost is formed will be defrosted faster than areas with heavy frost formation. These early defrosted areas will, during the
25 remaining defrosting cycle for defrosting the areas with heavy frost formation, transfer excessive heat from the defrosting heater to the ambient air. Thereby, a most unwanted heating of the air in the compartment is caused together with an excessive energy consumption of the heater. Further, during
30 defrosting, the uneven heat distribution over the fins per se causes some areas of the fins to be defrosted earlier than

other areas, thereby creating the same disadvantages as just mentioned.

The above-described problems connected with the prior art defrosting arrangements are particularly severe in conjunction with mobile absorption refrigeration applications. At such applications, the physical dimensions of the refrigerator cabinet, i.e. maximal allowable height of the cabinet, limit the total cooling capacity of the refrigeration apparatus. Thus, any excessive heat added directly to the evaporator or the air in the refrigerator compartments, drastically reduces the possibility to keep the compartments at temperatures as low as nowadays desired. Further more, at some mobile applications the available electrical DC energy is often limited. Thus, an excessive energy need for defrosting is most unwanted and might even lead to battery drainage causing downtime or collapse in the various electrical systems of the vehicle.

Brief summary of the invention

The general object of the present invention is therefore to provide a heat exchanger arrangement comprising a heat exchanger and a defrosting means, which arrangement permits defrosting of the heat exchanger while eliminating or reducing the above-mentioned problems.

A particular object is to provide such an arrangement, which permits energy efficient defrosting of the heat exchanger.

A further object is to provide such an arrangement, which permits defrosting of the heat exchanger, while minimizing the heat transfer from the defrosting heater to the refrigeration medium carried by the evaporator.

A still further object is to provide such an arrangement, which allows for relatively short defrosting cycles at relatively long intervals.

These objects are achieved with an arrangement according to the first paragraph of this description, at which arrangement the heat-conducting member is arranged essentially between the heat generating element and the evaporator tube. By arranging the heat conducting member between the heating element and the evaporator tube it is guaranteed that the evaporator tube is positioned at the greatest possible heat conducting distance from the heating element. By this means, all defrosting heat, generated by the heating element is forced to pass the entire heat-conducting member before it reaches the refrigeration medium in the evaporator tube. Hereby, the entire amount of heat generated by the defrosting heater is utilized for defrosting the heat-conducting member at the same time as the refrigeration medium and the refrigeration apparatus are not loaded with excessive absorption of defrosting heat.

Further objects and advantages of the invention are set out in the depending claims.

Detailed description of the invention

Exemplifying embodiments of the invention will now be described with reference to the drawings, in which:

Fig. 1 is a schematic side elevation from behind of a portion of a first embodiment of an evaporator according to the invention.

Fig. 2 is an enlarged cross section along line II in fig. 1, also representing a sidewall of a refrigerator cabinet.

Fig. 3 is a view corresponding to fig. 2 of a second embodiment of the invention.

In figure 1 a part of an evaporator 1 is shown as seen from the back of a refrigerator cabinet with the rear wall 3 (see fig. 2) removed. The evaporator forms part of an absorption refrigeration system including a boiler, an absorber, a condenser and an evaporator tube. The refrigerator cabinet comprises an upper freezer compartment and a lower refrigerator compartment. The temperature in the freezer is typically kept at approx. -15° to -18° C and in the refrigerator at approx. $+4$ to $+8^{\circ}$ C. The freezer is cooled by an upper upstream portion 2 of the evaporator tube. This portion 2 of the evaporator tube comprises four straight tube sections 2a and three tube bends 2b. The straight tube sections 2a are arranged vertically one above the other and connected one after the other by respective tube bend 2b. The freezer portion 2 of the evaporator tube thus extends in a generally vertical extension plane, defined by the straight tube portions 2a and the tube bends 2b. As best seen in fig 2, the freezer portion 2 of the evaporator is arranged in proximity to the rear wall 3 such that an air circulation gap 4 is formed between the evaporator tube 2a, 2b and the rear wall 3. The downstream end 2c of the freezer portion 2 of the evaporator is connected to the remaining downstream evaporator tube (not shown), which comprises a refrigerator portion of the evaporator tube, which is arranged in the refrigerator compartment.

A heat exchanger 5 in the form of a fin package is arranged in heat conducting contact with the freezer portion 2 of the evaporator. The heat exchanger 5 is attached to the vertical side of the evaporator portion 2, which vertical side is opposite to the rear wall 3. The heat exchanger 5 comprises a first heat distributing base plate 6, which is in contact with the evaporator tube 2a, 2b. A plurality of heat conducting

members 7 in the form of fins extends perpendicular from the base plate 6. In their vertical longitudinal direction, the fins 7 extend over the entire height of the base plate 6. The fins 7 exhibit first 7a and second 7b vertically extending side edges, the second side edges 7b being opposite to the first 7a. The first side edges 7a are arranged in contact with the base plate 6.

A second heat distributing plate 8 is arranged in heat conducting contact with the second side edges 7b of the fins 7. The second heat distributing plate 8 has essentially the same dimensions as the base plate 6 and is arranged in parallel with the base plate 6. The heat exchanger 5 thus comprises the base plate 6, the fins 7 and the second heat distributing plate 8 and forms there between vertically extending air channels 9. In the shown embodiment the heat exchanger 5, is formed in one integral piece, through extrusion of aluminum.

A heating element 10 for defrosting the heat exchanger and the evaporator tube 2a, 2b is glued or by other means attached to one side of the second heat distributing plate 8, which side is opposite to the fins 7, the base plate 6 and the evaporator tube 2a, 2b. A resistive film constitutes the heating element 10. The resistive film covers essentially the entire side surface of the second heat distributing plate 8.

During normal operation of the refrigeration cabinet, the resistive film 10 is inactivated and the refrigeration apparatus is in operation. Air in the freezer compartment circulates by self-circulation downwards through the channels 9 and the gap 4. During passage through the channels 9 and the gap 4, heat is transferred from the air, through the material in the heat exchanger 5 and evaporator tube 2a, 2b, to the

interior of the evaporator tube, where it is absorbed by the cooling medium and transported downstream through the remaining evaporator tube to the absorber. During this process the temperature of the cooling medium is typically approx. -30° C at the upstream entrance 2d of the freezer portion 2 of the evaporator. At the downstream end 2c of this evaporator portion 2, the temperature of the cooling medium has typically risen to approx. -24° C. This difference in temperature of the medium would, in the prior art arrangements, cause a significant difference in surface temperature between different areas of the heat exchanger. Also other aspects, such as the geometry and the thickness of the material of the heat exchanger would contribute to such local variations in surface temperature. The different surface temperatures would in turn cause uneven formation or build-up of frost on the heat exchanger, leading to the problems as discussed earlier in this application.

At the evaporator according to the invention however, the first 6 and second 7 heat distributing plates contributes in a large extent to equalize the temperature over the entire surface of the heat exchanger. Hereby, the formation of frost will take place at an essentially equal rate over the entire heat exchanger 5. This in turn, reduces the risk for local clogging of air passages and makes it possible to prolong the intervals between the defrosting cycles.

During defrosting, the refrigeration apparatus is deactivated and the resistive film 10 is heated by connecting an electrical voltage. The heat generated by the resistive film 10 is conducted from the film 10 to the second heat distributing plate 8 and further through the fins 7 to the first heat distributing plate 6. Since the entire heat exchanger 5, according to the invention, is located between

the heating film 10 and the evaporator tube 2a, 2b all heat generated by the film 10 has to pass through the entire cross section of the heat exchanger before it reaches the evaporator tube 2a, 2b. Or expressed differently, since the evaporator tube 2a, 2b is located at the greatest possible heat conducting distance from the heating film 10, no heat has to pass the evaporator tube in order to reach any part of the heat exchanger 5. Hereby it is achieved that the refrigeration medium is not loaded with excessive heat from the defrosting heater. Further more the first 6 and second 8 heat distributing plates contributes to an even distribution of the defrosting heat over the heat exchanger. This in combination with the above-described even formation of frost, results in that the entire heat exchanger will be fully defrosted at essentially the same time. No local area of the heat exchanger will therefore dissipate excessive heat to air in the compartment because of completed defrosting of that area and subsequent local overheating earlier than other areas.

With a heat exchanger arrangement according to the invention defrosting is thus carried out in an energy efficient manner.

Figure 3 shows a simplified embodiment of the invention. In this embodiment the heat exchanger is constituted by a single heat conducting plate 11, which is attached in heat conducting contact to the freezer portion 2 of the evaporator and arranged in parallel to the general extension plane of this portion 2. A resistive film 10 constitutes the defrosting heating element. According to the invention, a first side surface of the heat-conducting plate is attached to the evaporator tube 2a and the heating element is arranged on the opposite side of the heat-conducting plate. This embodiment may be used e.g. in small compartments which do not require a large heat exchanger area.

Above, two exemplifying embodiments of the evaporator according to the invention have been described. The invention may however be varied in a many different ways within the scope of the appended claims. For instance, instead of being used in the freezer compartment of a two-compartment refrigerator cabinet, the evaporator may be applied in any compartment of a cabinet having any number of compartments. The heat exchanger may, instead of being arranged on a side of the evaporator tube facing away from the rear wall of the compartment, be arranged on any side of the evaporator tube, such as behind, above or beneath. The evaporator portion carrying the heat exchanger may be arranged near the rear wall as described above, but it may also be arranged at any other location inside a compartment as well as fully or partly embedded or enclosed in any of the walls surrounding a compartment. The heat exchanger may have any suitable configuration, as long as the surfaces for contacting air are arranged essentially between the defrost heating element and the evaporator tube. It may e.g. comprise single or multiple fins, baffles, flanges, plates or the like, which may be arranged in parallel with or at an angle to each other and at any suitable angle to the evaporator tube. It may also comprise other surface enlarging elements e.g. wool, such as steel wool or aluminum wool or members having e.g. circular, oval or polygonal cross section. The heat exchanger may be of any suitable material and formed of one single integral member or of a plurality of members interconnected by soldering, gluing, riveting or by other means.

Claims

1. Heat exchanger arrangement for a refrigerator apparatus,
which arrangement comprises an evaporator tube (2) for
conducting a refrigerating medium; a heat exchanger (5, 11)
5 with at least one heat conducting member (7, 11), which is
arranged in heat conducting contact with a portion of the
evaporator tube and; a heat generating element (10) for
defrosting the heat exchanger, which element is arranged in
heat conducting contact with the heat conducting member,
10 **characterized in**
that the heat conducting member (7, 11) is arranged
essentially between the heat generating element (10) and the
evaporator tube (2).
2. Arrangement according to claim 1, wherein the heat
15 generating element (10) and the evaporator tube (2) are
arranged at opposite sides of the heat conducting member (7).
3. Arrangement according to claim 1 or 2, wherein the heat
conducting member (7) comprises a flat surface, the heat
generating member (10) and the evaporator tube (2) being
20 arranged at opposite edges (7a, 7b) of the flat surface.
4. Arrangement according to any of claims 1 - 3, wherein the
heat-conducting member constitutes a fin (7).
5. Arrangement according to claim 4, comprising a plurality of
fins (7), which are arranged essentially in parallel to each
other.
25
6. Arrangement according to any of claims 1 - 5, wherein a
first heat distributing plate (6) is arranged between the
evaporator tube (2) and the heat-conducting member (7).

7. Arrangement according to any of claims 1 - 6, wherein a second heat distributing plate (8) is arranged between the heat generating element (10) and the heat-conducting member (7).

5

8. Arrangement according to claim 7, wherein the heat conducting member (7) and the first and second heat distributing plates (6, 8) form an integral member (5).

9. Arrangement according to claim 8, wherein the integral member (5) is extruded, preferably of aluminum.

10

10. Arrangement according to any of claims 1 - 9, wherein the evaporator tube (2) is arranged in a first extension plane and a plurality of heat conducting members (7) are arranged essentially perpendicular to said first extension plane.

15

11. Arrangement according to claim 10, wherein the evaporator tube (2) is formed with at least one tube bend (2b), which defines the extension plane of the evaporator tube; the first heat distributing plate (6) is arranged in contact with the evaporator tube and in parallel with the extension plane; the fins (7) are arranged on the first heat distributing plate (6) such that a first edge (7a) of each fin makes contact with that side of the first heat distributing plate which is opposite to the evaporator tube and such that each fin extends generally perpendicular to the second heat distributing plate; the second heat distributing plate (8) is arranged generally in parallel with the first heat distributing plate and in contact with second edges (7b) of the fins, which second edges are opposite to the first edges (7a); and the heat generating element (10) is arranged on that side of the second heat distributing plate, which side is opposite to the fins.

20

25

30

13. Refrigerator cabinet comprising a heat exchanger arrangement according any of claims 1 - 12.

13. Refrigerator cabinet comprising a heat exchanger arrangement according any of claims 1 - 12.

Abstract

Heat exchanger arrangement for a refrigerator apparatus, which evaporator comprises an evaporator tube (2) for conducting a refrigerating medium; a heat exchanger (5, 11) with at least one heat conducting member (7, 11), which is arranged in heat conducting contact with a portion of the evaporator tube and; a heat generating element (10) for defrosting the heat exchanger, which element is arranged in heat conducting contact with the heat conducting member. For optimizing defrosting, the heat-conducting member (7, 11) is arranged essentially between the heat generating element (10) and the evaporator tube (2).

Fig. 2



Fig.1




Fig.2




Fig.3

